



TEFRA

Technical information

Size class: 3 - 4 T		
Pin diameter pick up 35mm or 40mm	Bottom frame width 117mm	Pin pick up range 162mm-217mm
Size class: 5 - 6 T		
Pin diameter pick up 40mm or 45mm or 50mm	Bottom frame width 143mm	Pin pick up range 216mm - 272mm
Size class: 7 - 8 T		
Pin diameter pick up 45mm or 50mm or 60mm	Bottom frame width 163mm or 183mm	Pin pick up range 279mm - 356mm
Size class: 13T		
Pin diameter pick up 60mm or 65mm	Bottom frame width 218mm or 248mm	Pin pick up range 345mm - 435mm
Size class: 16T		
Pin diameter pick up 70mm or 80mm	Bottom frame width 277mm or 298mm	Pin pick up range 386mm - 510mm
Size class: 21T		
Pin diameter pick up 80mm	Bottom frame width 277mm or 298mm	Pin pick up range 386mm - 510mm
Size class: 25T		
Pin diameter pick up 80mm	Bottom frame width 298mm	Pin pick up range 386mm - 510mm
Size class: 30T		
Pin diameter pick up 90mm	Bottom frame width 378mm	Pin pick up range 455mm - 572mm
Size class: 35T		
Pin diameter pick up 90mm or 100mm	Bottom frame width 400mm	Pin pick up range 517mm - 650mm
Size class: 45T		
Pin diameter pick up 100mm or 110mm	Bottom frame width 442mm	Pin pick up range 517mm - 650mm

- ✓ Tefra couplers in 50 ton/65 ton/75 ton and 100 ton can be made to special order.
- ✓ We can also manufacture Mix and Match Tefra couplers to fit any special attachment size